

# CC 28

## Combustible Gas Detector



## CC 28 Fixed Transmitter

- Full featured smart transmitter for combustible gas measurement
- Non-intrusive Autocal® calibration
- Expected sensor life of 5 years
- Increased safety design to reduce installation cost in potentially hazardous locations
- ATEX EEx dem [1b] IIC T4
- Proprietary, high performance combustible gas sensor
- Available in three configurations:
  - Blind (no display)
  - Display
  - Display with local alarms

**GfG Instrumentation**

1194 Oak Valley Dr, Ste 20, Ann Arbor MI 48108 USA  
(800) 959-0329 • (734) 769-0573 • [www.gfg-inc.com](http://www.gfg-inc.com)

# CC 28 - The Smart Transmitter for Combustible Gases

## Superior Technology

In areas where combustible gas or vapor hazards may exist, GfG's new CC 28 combustible transmitter is the perfect choice for reliable area monitoring. With its proven design, this ATEX certified transmitter offers an integrated explosion-proof buzzer and bright alarm LEDs for reliable warning of combustible gas hazards (even in hazardous locations). This superior design provides warning for immediate personnel, and ensures entire plant safety.

## Easy Handling

Smart sensor technology allows easy installation. Sensor replacement takes only a few seconds - simply plug in the sensor. User adjustments are performed at the transmitter with simple touch keys, or with the optional remote control interface (one person calibration).

## RC2 remote control

Several combustible gases are lighter than air. With the transmitter mounted close to the ceiling, calibration can be difficult. The remote control for the CC 28 allows you to perform calibration or zero adjustments without the need of a ladder or lift. A flexible cable connects the remote control to the transmitter and displays the same reading as the display on the transmitter. With the remote control inspection, service and calibration can be performed easily by one person.

The sensor and the integrated temperature compensation provide for the highest measurement accuracy.

Low maintenance requirements and long sensor life reduce your cost of ownership. Just sign a service contract and don't worry about any problems. We will service your systems at regular intervals.

## Models

The CC 28D allows you to read the gas concentration both at the transmitter and at the GMA controller.


The CC 28DA provides additional warning with bright integrated alarm LEDs and a buzzer.



## Advantages at a glance:

- Display of gas concentration at transmitter or remote control
- ATEX II G EEx dem [ib] IIC T4
- Ex-proof visual and audible alarms
- No need of expensive EX-proof buzzer or wiring
- Easy sensor replacement with plug-in sensors
- Long life sensor
- Low service requirement
- Permanent status and function display at transmitter
- Adjustments by means of touch keys or remote control without opening the casing
- Easy handling even at hard-to-reach accessible transmitter positions.

## Specifications

<b>Gases</b> Combustible gases and vapors	<b>Casing protection</b> IP 64	<b>Weight</b> 28 ounces (800 grams) with display
<b>Detection range</b> 0 - 100% LEL 0 - 50% LEL	<b>Display</b> 4-digit LED for linearized detection values and messages. LEDs for operation/fault.	<b>Dimensions</b> 7.63x3.94x2.17 inches (193x100x55 mm) (HxWxD)
<b>Detection Principle</b> Catalytic combustion	<b>Function Keys</b> 3 touch keys for all settings/calibration, function test	<b>Ratings and Certifications</b> ATEX II 2 G EEx dem [ib] IIC T4 0158 EC-Type BVS 04 ATEX E 132 X EMC EN 50270: 1999 Radioshielding: Type class I Interference resistance: Type class II
<b>Ambient temperature</b> -4 to +122°F / -20 to +50°C	<b>Transmitter Cable</b> Shielded cable 3 x 0.75 mm <sup>2</sup> for up to 200 m, 3 x 1.5 mm <sup>2</sup> for up to 1,000 m, M 16 x 1.5	QM system certified DIN E1N ISO 
<b>Output signal</b> 4-20 mA	<b>Expected Sensor Life</b> 3-5 years	
<b>Supply Voltage</b> 24 VDC		

Specifications subject to change without notification

Distributed by:



**GfG Instrumentation**

Tel: (800) 959-0329 or (734) 769-0573  
Fax: (734) 769-1888  
E-mail: info@gfg-inc.com  
Website: www.gfg-inc.com